


Antenna Mast / Turntable Controller AMTTC-300

Features:

- Multi device control (up to three independent channels)
- Variable speed control (only for Turntable)
- Fiber optic interface with antenna mast and turn table eliminates RF noise
- Full control through front panel or PC software
- Allows on-site calibration of antenna mast and turn table
- 19", 3U rack mountable
- 3 years warranty



Description:

Com-Power model AMTTC-300 Antenna Mast / Turntable Controller provides fully automated control of Com-Power Antenna Mast & Turn Table.

Specifications:

Channels	Up to three independent channels
Channel Interface	Fiber Optic via Duplex VL (Avago duplex latching POF versatile link jack)
Fiber Optic Cable	10 Meter VL/VL duplex crossover POF (up to 30 mtr optional available)
PC Interface	USB 2.0
Operation Control	Front Panel or PC software
Display	16 x 2 Alphanumeric LCD
Software Limit	Always displayed on front panel Can be turned on and off using front panel or PC software
System Input Power	100 – 250 Vac, 50 Hz / 60Hz (100 VA Max.)
Fuse Type	1 Amps (T)
Weight	13 lbs (5.9 Kgs)
Dimensions (H x W x D)	7.75" x 19" x 13.5" (19.7 x 48.3 x 34.3 cm) (excluding handles)
Operating Temperature	40°F to 104°F (5°C to 40°C)