

TSS 500N2F

TELECOM SURGE GENERATOR



FOR TESTS ACCORDING TO ...

- > FCC 97-270 (part 68)
- > TIA-968-B

TSS 500N2F - TELECOM SURGE GENERATOR FOR SURGE A PULSES AS PER FCC PART 68

Telecommunication networks are exposed to lightning events. Therefore telecommunication equipment being connected to the outside world need to have appropriate protection to show an acceptable immunity to surge transients in order not to fail in case of lightning events. Telecom Surge Simulators of the TSS 500N series are used to proof the immunity of telecommunications equipment.

The TSS 500N2F is used for Surge A pulse testing and AC power line surge testing as per TIA-968-B and FCC 97-270 (part 68).

HIGHLIGHTS

- > **FCC part 68 Surge A and Power line surge**
- > **Includes pulses 2/10us, 10/560us and 10/160us**
- > **Auto-setting of source impedance for each pulse**
- > **Built-in CDN for Telecom ports**
- > **Built-in CDN for AC power ports**
- > **Standard Test routines**
- > **Manual operation**
- > **USB and GPIB interface**

APPLICATION AREAS

-  COMPONENTS
-  TELECOM

TECHNICAL DETAILS

STANDARD IMPULSES

TIA-968-B (2009)	Pulse 10/160 us, Type A Pulse 10/560 us, Type A Pulse 2/10 us, Power line surge
FCC 97-270 (part 68)	Pulse 2/10 us Pulse 10/160 us Pulse 10/560 us

POWER LINE SURGE, PULSE 2/10 US

Voltage (o.c.)	160 V - 2,500 V
Rise time	2 μ s +0/-1 μ s
Pulse duration	10 μ s +9/-0 μ s
Current (s.c.)	> 64 A - 1,000 A
Rise time	2 μ s +0/-1 μ s
Pulse duration	10 μ s +9/-0 μ s
Polarity	Positive, negative or alternating
Counter	1 - 30,000 or endless

SURGE A LONGITUDINAL, PULSE 10/160 US

Voltage (o.c.)	160 V - 1,500 V +10/-0%
Rise time	10 μ s +0/-4 μ s
Pulse duration	160 μ s +100/-0 μ s
Current (s.c.)	20 A - 200 A per wire +15/-0%
Rise time	10 μ s +0/-5 μ s
Pulse duration	160 μ s +50/-0 μ s
Polarity	Positive, negative or alternating
Counter	1 - 30,000 or endless

SURGE A METALLIC, PULSE 10/560 US

Output voltage open circuit	160 V - 1,000 V +10/-0%
Rise time	10 μ s +0/-4 μ s
Pulse duration	560 μ s +300/-0 μ s
Current (s.c.)	10 A - 100 A per wire +15/-0%
Rise time	10 μ s +0/-5 μ s
Pulse duration	560 μ s +200/-0 μ s
Polarity	Positive, negativ or alternating
Counter	1 - 30,000 or endless

COUPLING

Telecom ports	T-R, T-G, R-G, T+R-G
Power ports	L-N, L-PE, N-PE, (250 V/16 A)

MEASUREMENTS

Peak voltmeter	2,500 V \pm 10%
Peak current meter	1,000 A \pm 10%

TRIGGER

Automatic	Automatic pulse release
Manual	Single pulse release
External	External pulse release
CRO trigger	5V trigger signal for oscilloscope
Synchronisation	0° - 360° (for ac power ports)

TEST ROUTINES

Quick Start	Immediate start; easy-to-use and fast
User Test routines	Manual Standard Test Routines Change Polarity after n pulses Change voltage after n pulses
Standard Test routines	Test pulses/levels as per FCC part 68
Service	Service, setup, self test

INTERFACE

Serial interface	USB
Parallel interface	IEEE 488, addresses 1 - 30
CN interface	To control external coupling network

SAFETY

Safety circuit	Control input (24 Vdc)
Warning lamp	Floating output contact

GENERAL DATA

Dimensions, weight	19 "/6 HU, approx. 35 kg
Supply voltage	115/230 V +10/-15%
Fuses	2 x 2 AT (230 V) or 2 x 4 AT (115 V)

OPTIONS

iec.control	Software to control the test, including standard library, test report facility and data conversion generator
-------------	--

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

AMETEK CTS GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland
 Phone +41 (0)61 204 41 11 > Fax +41 (0)61 204 41 00
 Internet: www.ametek-cts.com > E-mail: sales.conducted.cts@ametek.com

Germany

AMETEK CTS Europe GmbH > Customer Care Center EMEA > Lünener Straße 211
 > 59174 Kamen > Germany
 Phone +49 (0) 2307 26070-0 > Fax +49 (0) 2307 17050
 Internet: www.ametek-cts.com > E-mail: info.cts.de@ametek.com

Poland

AMETEK CTS Europe GmbH > Biuro w Polsce > ul. Twarda 44 > 00-831 Warsaw > Poland
 Phone +48 (0) 518 643 12
 Internet: www.ametek-cts.com > E-mail: Infopolska.cts@ametek.com

USA / Canada

AMETEK CTS US > 52 Mayfield Ave > Edison > NJ 08837 > USA
 Phone +1 732 417 0501
 Internet: www.ametek-cts.com > E-mail: usasales.cts@ametek.com

P.R. China

E & S Test Technology Limited > Rm 913, Leftbank >
 No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
 Internet: www.emtest.com > E-mail: info@emtest.com.cn

Republic of Korea

EM TEST Korea Limited > #405 > WooYeon Plaza > #986-8 > YoungDeok-dong >
 Giheung-gu > Yongin-si > Gyeonggi-do > Korea
 Phone +82 (31) 216 8616 > Fax +82 (31) 216 8616
 Internet: www.emtest.co.kr > E-mail: sales@emtest.co.kr

Singapore

AMETEK Singapore Pte. Ltd > No. 43 Changi South Avenue 2 > 04-01 Singapore
 48164
 Internet: www.ametek-cts.com > E-mail: singaporesales.cts@ametek.com

Great Britain

AMETEK GB > 5 Ashville Way > Molly Millars Lane > Wokingham > Berkshire
 RG41 2 PL > Great Britain
 Phone +44 845 074 0660
 Internet: www.ametek-cts.com

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.